OEXION Docks Hydraulic System





Product Overview

- Bridge gap & height differences between truck and warehouse floor to enable safer, smooth and efficient loading and unloading operation.
- Durable oven-baked epoxy powder-coat finishing - first and only in the world.
- "Seamless" joint deck for easy maintenance and enhanced durability.
- Single push-button control for easy operation to raise stored Dock Leveller to floor position and lip extension.

- Open-style self-cleaning lug-type lip hinge design with 270% more support on lip & deck.
- European technology hydraulic power unit.
- High tensile lip & deck safety tread plate.
- Open design sub frame for easy pit cleaning.
- Safety toe guards open and close automatically.
- 100mm of side to side tilt with no pinch point.
- Heavy duty laminated rubber bumper provides durable protection.
- Security night locks.



Project reference with Dexion Dock Levellers

Technical Specifications

- Standard capacity from 11 tonnes to 18 tonnes.
- Operating range 305mm above & below deck.
- Power supply 240 Volt, Single Phase/50Hz.
- Colour: Anthracite Grey (RAL 7016).
- Customised Dock Levellers available on enquiry.

MODEL	DECK SIZE	LIP	CAPACITY	PIT SIZE (mm)			
	mm	mm	tonne	width (mm)	length (mm)	depth (back)	depth (front)
DH6x8-11	W1830 x L2210	406	11	1880 (-0/+10)	2210 (-0/+10)	495	500
DH6x8-13			13				
DH6x8-15			15				
DH6x8-18			18				
DH6x10-11	W1830 x L2825	406	11	1880 (-0/+10)	2825 (-0/+10)	495	500
DH6x10-13			13				
DH6x10-15			15				
DH6x10-18			18				
DH7x8-11	W2100 x L2210	406	11	2160 (-0/+10)	2210 (-0/+10)	495	500
DH7x8-13			13				
DH7x8-15			15				
DH7x8-18			18				
DH7x10-11	W2100 x L2825	406	11	2160 (-0/+10)	2825 (-0/+10)	495	500
DH7x10-13			13				
DH7x10-15			15				
DH7x10-18			18				

Contact our reps to find out what the best solution is for your business!

To find out more about Dexion Dock Levellers, call +603 5520 6000 or email contact@dexion.com.my

Disclaimer:

The Information contained herein is the intellectual property of Dexion Asia Sdn Bhd (Dexion). The Information is defined to include: data, text, images, specification, graphics, design details and any and all other information whatsoever contained herein. The Information has been produced exclusively for Dexion and may not be used for any other purpose. None of the information may be used, altered, edited, copied, distributed or duplicated in any way without the express written consent of Dexion. Whilst the utmost care is taken to ensure the accuracy of the information contained herein, Dexion makes no guarantee as to its accuracy. Dexion shall, under no circumstances, be liable for any costs, losses, expenses or damage which may in any way be attributable to the use or adoption of such data and/or design details. All dimensions indicated are nominal only. Dexion reserves the right to alter or amend any of the information herein, including data and design details, without prior notice.

